



włączenie się do bieżn. nawierzchni

km 0+000,00




Pm=0,14m²
P=0,50m

km 0+015,50




Pm=0,10m²
P=0,50m

km 0+026,50



Pm=0,08m²
P=0,50m

km 0+060,00




Pm=0,12m²
P=0m

km 0+075,50




Pm=0,10m²
P=0m

km 0+091,00




Pm=0,16m²
P=0m

km 0+105,00




Pm=0,04m²
P=0m

km 0+120,00




Pm=0,08m²
P=0m

km 0+134,50




Pm=0,20m²
P=0m

km 0+146,00




Pm=0,26m²
P=0m

km 0+163,00




Pm=0,20m²
P=0m

km 0+179,00




Pm=0,26m²
P=0m

km 0+197,00




Pm=0,38m²
P=0m

km 0+217,00




Pm=0,44m²
P=0m

km 0+233,00




Pm=0,34m²
P=0m

km 0+263,00




Pm=0,22m²
P=0m

km 0+276,50



Pm=0,26m²
P=0m

km 0+292,62



Pm=0,12m²
P=0m

km 0+307,62



Pm=0m²
P=0m

włączenie się do bieżn. nawierzchni

OGÓŁEM:

Pm - wyrównanie MMA - 56,66m 3

P - poszerzenia - 35,00m2

UWAGA!

Grubość profilowania mieszankami mineralno-asfaltowymi AC 11W poniżej 2cm połączyć z warstwą wiążącą z betonu asfaltowego AC 16W.

PRZEKROJE POPRZECZNE

LEGENDA :

Pm - pow. wyrównania MMA [m²]

P - poszerzenia [m]